IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Gilder et al.

Art Unit : Unknown Examiner : Unknown

Serial No. : Filed :

Title

: SAFETY RAZORS

Commissioner for Patents Washington, D.C. 20231

PRELIMINARY AMENDMENT

Prior to examination, please amend the application as follows:

In the specification:

Replace the paragraph beginning at page 1, line 2 with the following rewritten paragraph:

-- This application is a divisional application of U.S. Serial No. 09/107,765, filed June 30, 1998, which is a continuation of U.S. Serial No.08/604,976, filed May 17, 1996, which is a 371 of PCT/US94/10717, filed September 22, 1994. --

In the claims:

Cancel claims 2 and 5.

Amend claim 1, 3 and 12 as follows:

1.(Amended) A safety razor blade unit comprising a guard, a cap, and a group of first, second, and third blades with parallel sharpened edges located between the guard and cap, the first blade defining a blade edge nearest the guard having a negative exposure not less than

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No	EL224672077US	
-----------------------	---------------	--

I hereby certify under 37 CFR $\S1$ 10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissionei for Patents, Washington, D C 20231

Date of Deposit

Signature

Typed or Printed Name of Person Signing Certificate

Attorney's Docket No.: 00216-396003 / Case 4225 B

Applicant: Gılder et al.

Serial No. : Filed :

Page : 2

-0.2mm, and the third blade defining a blade edge nearest the cap having a positive exposure of not greater than +0.2mm.

3. (Amended) A safety razor blade unit according to claim 1, wherein a span between the first blade edge and the guard is in the range of 0.5mm to 1.5mm.

12. (Amended) A safety razor blade unit according to claim 1 wherein a span between the first blade edge and the guard is substantially smaller than the span between the edges of the first and second blades and a span between the edges of the second and third blades.

In the abstract:

Replace the abstract with the following version.

-- A safety razor blade unit including a guard, a cap, and a group of first, second, and third blades with parallel sharpened edges located between the guard and cap, the first blade defining a blade edge nearest the guard having a negative exposure not less than - 0.2 mm, and the third blade defines a blade edge nearest the cap having a positive exposure not greater than +0.2mm. --

For special large of the first that the second seco

Applicant: Gilder et al.

Serial No. : Filed : Page : 3

REMARKS

Attached is a marked-up version of the changes being made by the current amendment.

Applicant asks that all claims be examined. Please apply any other charges or credits to Deposit Account No. 06-1050.

Respectfully submitted,

Date: 17, 2001

William E. Booth
Reg. No. 28,933

Fish & Richardson P.C. 225 Franklin Street Boston, MA 02110-2804 Telephone: (617) 542-5070 Facsimile: (617) 542-8906

20243410 doc

Applicant: Gilder et al.

Serial No. : Filed : Page : 4

Version with markings to show changes made

In the specification:

Paragraph beginning at page 1, line 2 has been amended as follows:

-- This application is a divisional application of U.S. Serial No. 09/107,765, filed June 30, 1998, which is a continuation of U.S. Serial No.08/604,976, filed May 17, 1996, which is a 371 of PCT/US94/10717, filed September 22, 1994.--

In the claims:

Claims 2 and 5 have been cancelled.

Claim 1, 3 and 12 have been amended as follows:

1.(Amended) A safety razor blade unit comprising a guard, a cap, and a group of first, second, and third blades with parallel sharpened edges located between the guard and cap, the first blade defining [the] <u>a</u> blade edge nearest the guard having <u>a negative</u> [an] exposure not [greater than zero] <u>less than -0.2mm</u>, and the third blade defining <u>a</u> [the] blade edge nearest the cap having <u>a positive</u> [an] exposure of not <u>greater than +0.2mm</u> [less than zero].

- 3. (Amended) A safety razor blade unit according to claim $\underline{1}$ [2], wherein \underline{a} [the] span between the first blade edge and the guard is in the range of 0.5mm to 1.5mm.
- 12. (Amended) A safety razor blade unit according to <u>claim 1</u> [any of claims 1 to 11] wherein <u>a</u> [the] span between the first blade edge and the guard is substantially smaller than the span between the edges of the first and second blades and a span between the edges of the second and third blades.